

2010 U-Cars Rules

1. Car Types: 1989 & newer American made ONLY. Ford, GM and Mopar. No turbo's or super charged. 4 cylinder cars only. Front wheel drive only. NO aftermarket fuel injectors. Cylinder heads can be shaved a minimal amount for cleanup. If it is not listed in these rules it must stay stock OEM as manufactured. STOCK means STOCK.

A. Must maintain 0 Deck Height .005 tolerance

2. Modifications allowed:

A. Remove air conditioner condenser and ac pump.

B. Remove inertia switch (fuel shutoff on Ford).

C. Remove rear seat.

D. Electric cooling fan may be wired to run constantly.

E. Ballast lead fastened.

F. Racing seat only. No Fiberglass seats. Seat mounted with the cage is highly recommended. Seat mount kits are available at most race part dealers.

3. Mandatory modifications:

A. A full NASCAR style rollcage is highly recommended. Maximum of 6 points mounted to the floorpan and subframe with the use of minimum ¼" plate steel welded and bolted securely. A minimum of 3 door bars on the driver side and 2 on the passenger side are recommended. No bars are to be extended forward of the front firewall. Doors may be skinned to allow the use of this style cage. Rollcage tubing must be a minimum of 1.75" x .095 welded seam steel tube. See cage diagram.

B. 5 Point racing harness mandatory. Must be mounted according to manufacturers specifications. Must have a visible SFI tag with year. Not to exceed 3 years old.

C. Fuel cell recommended. If aftermarket fuel cell is used it can be mounted in the trunk area. If a stock gas tank is retained, it must have additional strapping around it.

1. If fuel cell is located in trunk area, a full rear firewall must be used. The entire trunk area must be closed off to the driver's compartment.

D. Window net on drivers side door.

E. Hood pins allowed front and rear.

F. Fire extinguisher within drivers reach.

4. Things that will be checked:

- A. Stock steel wheels **only**, stock suspension in stock location.
- B. 4 wheel working stock brakes, stock steering column must start with key.
- C. Stock transmission.
- D. No locked differential.
- E. **Racing Seat Only. No Fiberglass or Stock Seats.**
- F. Stock dash board with no alterations.
- G. Stock door panels with no upholstery. No metal removed.
- H. No body modifications. Stock ride height. No removing of metal such as hoods, trunks and doors. All body metal must remain in place.
- I. All engine components must be stock for engine. No crossbreeding of parts.
- J. Battery may be moved to behind driver seat only if in approved battery box and bolted to the floor.
- K. Must have stock muffler - Cannot be altered or modified in any way, although it may be re-routed as long as all original parts are retained. NO Glasspacks, Cherry Bombs, etc. If we can hear it, It's too loud.
- L. No ABS traction control style braking systems. Must be disconnected.

5. What needs to be removed:

- A. Back seat. Opening covered with sheet metal, no holes.
- B. Other upholstery.
- C. All lights and chrome.
- D. Stock windshield dimensions must be retained. Can use glass or Lexan

6. Driver must have a fireproof suit and a Snell 95 approved helmet.

- A. Vehicle must be equipped with a 2.5 lb fire extinguisher.
- B. Driver must wear firesuit, helmet, gloves and neck collar.

7. Minimum weight:

Single Overhead Cam – 2400# w/ driver

Dual Overhead Cam – 2700# w/ driver

- a. All added weight must be painted white and securely mounted in place with your car number on weight.
- b. Any added weight must have more than one bolt with washers.
- c. Speedway reserves the right to add weight to any competitor winning 3 or more races to equalize competition. Weight may be required to be placed in a specific location on the car.

8. Engine must remain to factory specifications, with the exception of a .030's overbore permitted. Pistons must be exact same configuration and weight as stock. K&N performance air filters permitted.

9. Wheels and tires:

- A. Stock Steel Wheels Only, must be same size on all four corners.
- B. Tire sizes permitted: Maximum 205/60 Maximum.

